



Versicarte Plus Finishes

Versicarte Plus's unique design enables a vast range of colours and finishes to be supplied, below are a sample of our Standard Range. Metalics, woods and natural textures are also available on request.












Coachlines and transfers are also available at extra cost.

Stelvetite Panel Colour Option (must be specified at time of order)



Note: Any panel colour changes after order has been processed may be chargeable.

- Default Colour is Merlin Grey
- * Extra cost applies to these finishes

Due to variations in monitors and printers the colours of manufactured panels may vary from what appears online. The images should be taken as indicative only and physical samples should be requested where the colour choice is critical.




COUNTERING

3

Versicarte Plus

Moffat's **Versicarte** food servery trolleys have been totally redesigned to meet your changing needs. The new **Versicarte Plus** range has been developed in consultation with school meals organisations, so as well as helping caterers comply with hygiene, HACCP, energy efficiency and healthy eating initiatives, these great-looking food service trolleys will help attract children to your meal service.

The new trolleys' streamlined design, including curved gantry, smooth body and semi obscured castors, is not just highly practical: the stylish lines will appeal directly to your young customers. What's more, the **Versicarte Plus** fascia panels can be easily changed. So if you want a fresh look in the dining area, simply change the panels







Versicarte Street Cart

Street Food style concept models

- optional gantry with glass shelf, overhead sign and bespoke magnetic board graphics.
- Low cost retail style solution ideal for school catering!
- Eye catching magnetic graphic panels can be easily swapped to suit changing menus
- Graphic design can be made to order and incorporate individual branding and artwork.



Example of chilled unit

Base unit **VCRW3** with
Fluorescent Type Gantry **VCFS3**Tray rail **VCTT3**and Graphics package **VCGR3** (bespoke artwork)

Example of Hot units

Base units VCBM2 with Quartz Gantry VCQS2 Tray rail VCTT2 and Graphics package VCGR2 (bespoke artwork)

Street Cart Graphics

| | VCGR2 | VCGR3 | VCGR4 | VCGR5 | VCGCS | VCGCU |
|-------|--------------|--------------|--------------|--------------|--------------|--------------|
| MODEL | Size 2 | Size 3 | Size 4 | Size 5 | Cash Unit | Corner Unit |
| | graphics kit |

Street Cart Gantries

Quarts lamp Illuminated gantry with glass shelf and overhead sign

| MODEL | VCQS2 | VCQS3 | VCQS4 | VCQS5 | | |
|--|-------|-------|-------|-------|--|--|
| Fluorescent lamp Illuminated gantry with glass shelf and overhead sign | | | | | | |

| 11.55 | MODEL | VCFS2 | VCFS3 | VCFS4 | VCFS5 |
|-------|-------|-------|-------|-------|-------|
|-------|-------|-------|-------|-------|-------|

Street Cart Graphics board break down

| Panel | Left Side | Right Side | Front | Over Head Sign |
|-------|--------------|---------------|-------|----------------------|
| VCGR2 | 1 | 1 | 1 | 1 |
| VCGR3 | 1 | 1 | 1 | 1 |
| VCGR4 | 1 | 1 | 1 | 1 |
| VCGR5 | 1 | 1 | 1 | 1 |
| VCGCS | 1 | - | 1 | - |
| VCGCU | - | - | 1 | - |

Versicarte Plus

Food safety and quality have always been at the heart of the Versicarte. The **Versicarte Plus** further enhances this; for example, hot cupboards are now fan-assisted to give fast, even heating and ensure the best quality.

And the famous **Versicarte** versatility has been further expanded. Innovative features include the glass screens that can be adjusted, so that the trolley can switch from self-service to assisted service easily.

The wide range of options allows most modules to be customised to your individual requirements.

Versicarte modules can be butted together to form a straight or angular service counter. Alternatively, stand alone units can be placed around the dining area to create a free-flow self-service environment.

New products in the range include the **Versicarte Plus** Salad Bar, designed to keep those healthy greens looking great and in tiptop condition.

The Versatile new **Versicarte Plus**: making food service as easy as A, B, C.



Removable grid shelves make cleaning easy and in heated and refrigerated units help air circulation.



Glass panel in self service position



Coiled flex keeps electrical connection tidy. Hooking the flex to the unit improves portability.



Glass panel in assisted service position





All Versicarte Plus units can be fitted with the option of a triple tube drop down tray slide or solid drop down tray slide



Gantry lighting is fitted with safety bulbs featuring an outer glass casing.



Lockable castors make moving and positioning of units effortless



Optional extras such as this menu holder can be added to each unit

MOFFAT

Versicarte Plus

Heated Top Deli Display

Models VHTDD3, VHTDD4

- Hot Tops are designed to keep pre-cooked food at serving temperature and are suitable for the display of most types of
- Complete with easy to clean full Gastronome size toughened glass thermo panels with built in elements that guarantee even heat distribution, with no cold spots distortion or discoloration.
- Aesthetic full front curved toughened glass screen and glass side panels for increased food display.
- · Fitted with an intermediate ambient toughened glass shelf.
- Open to rear display case for easy access.
- · Optional sliding Perspex doors to rear.
- The energy regulated surface temperature is controlled at approximately 90° the controls are housed conveniently within the over head gantry for easy access.
- The quartz heated illuminated gantry is mounted above the hot top for increased heat and food presentation.





Regeneration Module

Model VCREG1

The Versicarte Plus Regeneration Module extends the Versicarte Plus Range to a new level. It enables you to put packs of chilled or frozen food directly into the oven where the food is regenerated ready for serving on the Thermo-Panel top. This is a "high efficiency" product as it saves lots of time and labour by reducing the movement and handling of food down to a minimum.

Energy efficiency also plays a big part in this product, the Multi-fan regeneration system, as used in the Moffat Versigen System, extracts the maximum heat from the power used. The Thermo-Panel top uses built-in elements to give even temperatures over the full area with no heat losses to the surrounding metal.

The exterior of the Versicarte Regeneration Plus is as all the specifications for all other Versicarte Plus Modules. The regeneration oven is all bright polished stainless steel construction, fully insulated, with side hinged door and slam catch. It has a capacity of 8 - 1/1 gastronorm at 70mm pitch. The Zone Control Flexibility enables it to regenerate high or low density food at the same time.

The Thermo-Panel top, all as described below, comes complete with overhead stainless steel gantry, fitted quartz heat/illumination featuring safety bulbs. A curved toughened glass full front sneeze guard is supplied which can be repositioned to form an overhead shelf and part front sneeze guard for self service.

Position Choice of front sneeze guard. The curved toughened glass sneeze guard/shelf has two positions as standard. Fitted as glass serving shelf and part front sneeze guard for self service, as shown in the main picture. Or, with full front screen guard and stainless steel serving shelf for assisted service.



Optional Solid Drop

Down Tray Slide







VCCP optional lift off carving plate to suit thermo glass panel.

hot cupboard



VCHT4 - Shown with optional triple tube drop down tray slide and coach lines. Gantry shown in self service position.

Hot Top, Inset with Glass Thermal Panels, plus Fan Assisted Hot Cupboard Models VCHT2, VCHT3, VCHT4, VCHT5

· Store hot food ready for serving.

- Illuminated on/off switch indicates power is on.
- · Top inset with toughened glass thermo panels with variable temperature control up to approximately 110°C.
- Thermostatically controlled hot cupboard with fan-assisted heating unit
- Sliding doors and all internal grid shelves are removable for cleaning.
- · Cupboard heating unit can easily be removed for maintenance and cleaning.
- Optional heated gantry with interchangeable curved glass screen. Quartz heated gantry with illuminated on/off switch



Forced air heating and recirculation which gives energy saving efficiency, faster heat up times, quicker heat recovery times and an even distribution of heat without troublesome hot spots.




VCBM4 - shown with optional triple tube drop down tray slide and coach lines. Gantry shown in self service position.

Dry Well Bains Marie with Hot Cupboard Models VCBM2, VCBM3, VCBM4, VCBM5

- Store hot food ready for serving.
- Illuminated on/off switch indicates power is on.
- · Thermostatically controlled Bain-marie with fanassisted heating unit.
- Designed to accommodate various combinations of interchangeable Gastronorm pans up to 150mm deep all Gastronorm pans sold separately please see price list for details.
- Sliding doors and internal grid shelves are removable for easy cleaning and maintenance.
- Optional heated gantry with interchangeable curved glass screen. Quartz heated gantry with illuminated on/off switch







Removeable grid shelves.

| MODEL |
|---------------------|
| Weight kg |
| Length mm |
| Height including |
| gantry mm |
| Depth mm |
| with trayslide up |
| with trayslide down |
| Work surf. Ht. mm |
| Dames satisfact |

1/1 Ga

| Length mm | 1190 | 1490 |
|--------------------|------|------|
| eight including | | |
| gantry mm | 1440 | 1440 |
| Depth mm | 680 | 680 |
| ith trayslide up | 950 | 950 |
| h trayslide down | 740 | 740 |
| rk surf. Ht. mm | 900 | 900 |
| ower rating kw | | |
| cluding gantry | 2.5 | 2.7 |
| cluding gantry | - | - |
| astronorm Capacity | 3 | 4 |
| Gastronorm panels | - | - |
| cupboard under | 1 | 1 |
| | | |

VHTD 90

| VHTDD4 | VCR |
|--------------------|--------------------|
| 120 | 95 |
| 1490 | 830 |
| 1440 680 950 | 1310 680 950 |
| 740 | 740 |
| 900 | 900 |
| 2.7 | 4.7 |
| - - | 4./ |
| 4 | - |
| - - | 2 |
| <u> </u> | |

| VCREG1 |
|---------------------------|
| 95 |
| 830 |
| 1310 680 950 740 |
| 900 |
| 4.7 |
| 2 |
| |

| VCHT2 | VCHT3 | VCHT4 | VCHT5 |
|---------------------------|---------------------------|---------------------------|---------------------------|
| 55 | 82 | 110 | 137 |
| 830 | 1160 | 1490 | 1815 |
| 1310 680 950 740 | 1310 680 950 740 | 1310 680 950 740 | 1310 680 950 740 |
| 900 | 900 | 900 | 900 |
| 2.1 | 2.5 | 2.7 | 2.6 |
| | | - | - |
| 2 | 3 | 4 | 5 |
| ✓ | √ | √ | √ |

| VCBM2 | VCBM3 | VCBM4 | VCBM5 |
|---------------------------|---------------------------|---------------------------|---------------------------|
| 45 | 67 | 90 | 112 |
| 830 | 1160 | 1490 | 1815 |
| 1310 680 950 740 | 1310 680 950 740 | 1310 680 950 740 | 1310 680 950 740 |
| 900 | 900 | 900 | 900 |
| 2.45 2.25 | 2.9 2.5 | 2.9 2.5 | 2.85 2.25 |
| 2 | 3 | 4 | 5 |
| - | - | - | - |
| 1 | 1 | 1 | ✓ |

| MODEL |
|---|
| Weight kg |
| Length mm Height including gantry mm Depth mm |
| with trayslide up with trayslide down |
| Work surf. Ht. mm |
| Power rating kw including gantry excluding gantry |
| 1/1 Gastronorm Capaci |
| No. of Gastronorm pane |
| Hot cupboard unde |
| |

MODEL

Versicarte Plus



VCRD4 - Shown with optional triple tube drop down tray slide.



MODEL

Weight kg

Length mm

gantry mm

Depth mm with trayslide up

Height including

with trayslide down

Work surf. Ht. mm

Power rating kw

including gantry

excluding gantry

cupboard under

1/1 Gastronorm capacity Refrigerated storage

Refrigerated Multi-Tier Display Unit with Ambient Shelf Under Models VCRD3, VCRD4, VCRD5

- · Refrigerated multi tier display unit with chilled well, three glass adjustable shelves and ambient shelf under.
- · Curtain of cold re-circulating air cascades down from top, ensuring even temperature of 2C to 8C.

WARNING

These units are not designed to operate in full mode for more than 24 hours, unless an optional front blind has been fitted.

- If the unit is to be used over a 24 hour period with the optional front blind, the blind should be pulled down as soon as possible after service has stopped
- · Stream of re-circulating cold air is blown up and across the display shelves and chilled well, ensuring temperature is maintained safely
- Glass display shelves are removable and have adjustable brackets.
- Chilled well has removable base sections for easy cleaning and maintenance.
- Automatic defrost cycle.
- Pull out condensate drip trav.



are also available with the option of a square top canopy combined with builtin lockable roller shutter. Shutters are supplied in white finish only, if coloured shutters are required these are priced on an individual basis. Please add the letters LSA after the codes below

and see price list for details.

· Refrigerated blown air well complete with ambient shelf under and optional illuminated gantry with interchangeable glass

VCRW4 - Shown with optional coach lines and solid drop

down tray slide. Gantry shown in assisted service position.

Models VCRW3, VCRW4, VCRW5

Refrigerated Well with Ambient Shelf Under

- · Re-circulating cold air blows across the display well ensuring an even temperature of 2C to 8C.
- · Chilled well has removable base sections for easy cleaning and maintenance.
- · Automatic defrost cycle.
- · Pull out condensate drip tray.

OPERATING CONDITIONS FOR REFRIGERATED WELL AND MULTI TIER DISPLAYS

IMPORTANT

To obtain the maximum performance and efficiency from these units it is imperative that the ambient room conditions where the units are being used do not exceed a temperature off 25C or exceed a relative room humidity of 60%.

WARNING


Should conditions exceed the above? The display units will not maintain food temperatures at required levels E&R Moffat cannot accept responsibility for the performance of the units being used in extreme conditions.

Versicarte Refrigerated Deli Display

Models VCRDD3, VCRDD4

- Chilled blown air wells are designed to keep pre-chilled food at a regulated serving temperature and are suitable for the display of most types of cold foods.
- · Complete with an inset well designed to provide a gentle flow of cold air maintaining a safe and compliant temperature within.
- Aesthetic full front curved toughened glass screen and glass side panels for increased food display.
- Fitted with an intermediate ambient toughened glass shelf.
- · Open to rear display case for easy access.
- · Optional Perspex doors to rear.
- The illuminated gantry is mounted above the well for increased food presentation
- · All models CFC free R404A refrigeration gas.
- Automatic defrost system
- · Pull out condensate drip tray.





- Do not install units where there is high solar radiated heat (for example, direct sunlight, room heaters or bright spotlights)
- When loading refrigerated display units for best performance and refrigeration efficiency a gap should be left between the products allowing the cold air to pass through and re-circulate.





Interior view of polar well.

Polar Plates

Polar plates must firstly be charged for 12/24 hours in a deep freeze. They are then placed inside the well where they give off a steady flow of cold air for a minimum of two hours. Once used, other polar plates can then be substituted thus keeping the well cold.

Polar Well with Polar Plates and Ambient Storage Cupboard Underneath Models VCPW2, VCPW3, VCPW4, VCPW5

- Polar well supplied with E&R Moffat Polar Plates, ambient storage cupboard, optional illuminated gantry and interchangeable glass screen.
- Polar Plates keep food chilled for 2 to 3 hours. Before use, the Polar Plates are charged for 8 to 12 hours in a deep freeze. If longer periods of operation are required, extra Polar Plates can be charged and used in rotation.
- Storage cupboard sliding doors are removable for easy cleaning.
- All internal shelves are removable for cleaning.
- Optional illuminated gantry with on/off switch indicating power is on.







VCPW4 - Shown with optional standard triple tube drop down trav slide.

MODEL

Weight kg

Length mm **Height including**

gantry mm

Depth mm

with trayslide up

with trayslide dowr

Work surf. Ht. mm

Power rating kw

including gantry

excluding gantry No. of 1/1 Polar Plates

Optional Solid Drop Down Tray Slide

Optional Triple Tube Drop Down Tray Slide

| VCRD3 Refrigerated D | VCRD4 isplay Ambient SI | VCRD5 helf Under | VCRW3 Refrigerated | VCRW4 Display Ambient S | VCRW5 helf Under |
|---------------------------|----------------------------|---------------------------|---------------------------|----------------------------|---------------------------|
| 156 | 208 | 260 | 127 | 170 | 212 |
| 1160 | 1490 | 1815 | 1160 | 1490 | 1815 |
| 1640 680 950 740 | 1640 680 950 740 | 1640 680 950 740 | 1310 680 950 740 | 1310 680 950 740 | 1310 680 950 740 |
| 900 | 900 | 900 | 900 | 900 | 900 |
| 2.0 | 2.0 | 2.0 | 1.5 1.4 | 1.5 1.4 | 2.0 1.9 |
| 3 | 4 | 5 | 3 | 4 | 5 |

| 1160 | 1490 | 1815 | 1160 | 1490 | 1815 |
|---------------------------|---------------------------|---------------------------|---------------------------|---------------------------|---------------------------|
| 1640 680 950 740 | 1640 680 950 740 | 1640 680 950 740 | 1310 680 950 740 | 1310 680 950 740 | 1310 680 950 740 |
| 900 | 900 | 900 | 900 | 900 | 900 |
| 2.0 | 2.0 | 2.0 | 1.5 1.4 | 1.5 1.4 | 2.0 1.9 |
| 3 | 4 | 5 | 3 | 4 | 5 |
| - | - | - | - | - | - |
| See nrice list | for detailed sr | ecification | | | |

| 1160 | 1490 | 1815 | 1160 | 1490 | 1815 | | | |
|---------------------------|---|---------------------------|---------------------------|---------------------------|---------------------------|--|--|--|
| 1640 680 950 740 | 1640 680 950 740 | 1640 680 950 740 | 1310 680 950 740 | 1310 680 950 740 | 1310 680 950 740 | | | |
| 900 | 900 | 900 | 900 | 900 | 900 | | | |
| 2.0 | 2.0 | 2.0 | 1.5 1.4 | 1.5 1.4 | 2.0 | | | |
| | | | | | | | | |
| 3 | - 4 | _ <u>5</u> | 3 | . 4 | 5 | | | |
| - | - | - | - | - | - | | | |
| See price li | See price list for detailed specification | | | | | | | |

| Ambient Shel | f Under |
|---------------------------|---------------------------|
| 150 | 200 |
| 1190 | 1490 |
| 1440 680 950 740 | 1440 680 950 740 |
| 900 | 900 |
| 2 | 2 |
| 3 | 4 |
| √ | <i>-</i> |

VCRND3 VCRND4

Note: Refrigerated units are designed for straight through ventilation. If units are to be placed against a wall alternative ventilation arrangements are available at extra cost.

| VCPW2 | VCPW3 | VCPW4 | VCPW5 |
|---------------------------|---------------------------|---------------------------|---------------------------|
| 58 | 87 | 117 | 145 |
| 830 | 1160 | 1490 | 1815 |
| 1310 680 950 740 | 1310 680 950 740 | 1310 680 950 740 | 1310 680 950 740 |
| 900 | 900 | 900 | 900 |
| 0.026 | 0.026 | 0.026 | 0.026 |
| 2 | 3 | 4 | 5 |
| - | - | - | _ |

Refrigerated storage cupboard under

1 1

Versicarte Plus Wall Unit Displays

This range contains all the attributes of the standard models, however, this design allows for the unit to be placed up to a wall.

The controls are mounted within the front panel for easy operator access.

The unit incorporates on board evaporation to avoid moving the unit to empty drip trays. An additional fan aids the compressor ventilation process.

Available for blown air and Multideck. The Multideck unit can be supplied with full size double glazed back panel or stainless steel back panel at the same cost. Double glazed doors come as standard.

These units do not come with refrigerated cuphoards under

- For full double glazed back panels
- · For full stainless steel back panels add SB to code

Note: All refrigerated units are available with refrigerated storage cupboard. Add 'R' to the end of the standard code. Please see price list for details.





Note: These models are also available with the option of a square top canopy combined with builtin lockable roller shutter. Shutters are supplied in white finish only, if coloured shutters are required these are priced on an individual basis. See LSA codes below and price list for details.



Refrigerated cold wells and vent panels designed to allow maximum air flow, enable us to offer improved energy efficiency and reduced running costs.



Refrigerated Multi-Tiered Display (Wall Unit) with Ambient Shelf Under Display Models VCRD3FC, VCRD4FC, VCRD5FC



Refrigerated Well (Wall Unit) with Ambient Shelf Under Well Models VCRW3FC, VCRW4FC, VCRW5FC

OPERATING CONDITIONS FOR REFRIGERATED WELL AND MULTI TIER DISPLAYS

IMPORTANT

To obtain the maximum performance and efficiency from these units it is imperative that the ambient room conditions where the units are being used do not exceed a temperature off 25°C or exceed a relative room humidity of 60%.

Should conditions exceed the above? The display units will not maintain food temperatures at required levels E&R Moffat cannot accept responsibility for the performance of the units being used in extreme conditions.

- Do not install units in draughty conditions where the air movement is greater than 0.2mtr./sec.
- (For example near entrance/ exit doors, open windows, under air conditioning vents or ceiling mounted fan).
- Do not install units where there is high solar radiated heat (for example, direct sunlight, room heaters or bright spotlights)
- When loading refrigerated display units for best performance and refrigeration efficiency a gap should be left between the products allowing the cold air to pass through and re-circulate.

Versicarte Grab and Go

Grab and go unit with three shelves. Use as standalone units or combined to create an attractive, mobile Food Servery Counter.



Heated display, open front, doors to rear, ambient cupboard Display Models VCGH2, VCGH3

Heated display, open front, solid rear, ambient cupboard Display Models VCGBH2, VCGBH3

Ambient display, open front, doors to rear, ambient cupboard Display Models VCGA2, VCGA3

Ambient display, open front, solid rear, ambient cupboard Display Models VCGBA2, VCGBA3

Weight kg Length mm Height including

MODEL

with travslide up with trayslide down

Power rating kw including gantry excluding gantry

Work surf. Ht. mm

1/1 Gastronorm capacity

Refrigerated storage cupboard under

| CRD3FC ersicarte refrigera | VCRD4FC ted multi tier display a | VCRD5FC mbient shelf under |
|-------------------------------|-------------------------------------|-------------------------------|
| .56 | 208 | 260 |
| .160 | 1490 | 1815 |
| 640 680 950 740 | 1640 680 950 740 | 1640 680 950 740 |
| 900 | 900 | 900 |
| 2.7 | 2.7 | 2.7 |
| 3 | 4 | 5 |
| | | |

| VCRD3FCLSA Versicarte refrigerated | VCRD4FCLSA multi tier display ambient she | VCRD5FCLSA elf under with lockable roller shutte |
|---------------------------------------|--|---|
| 166 | 218 | 270 |
| 1160 | 1490 | 1815 |
| 1800 680 950 740 | 1800 680 950 740 | 1800 680 950 740 |
| 900 | 900 | 900 |
| 2.7 | 2.7 | 2.7 |
| 3 | 4 | 5 |
| - | - | - |

| MODE | |
|---------------------------------------|--|
| Weight k | |
| Length mr | |
| Height including | |
| gantry mn | |
| Depth mn | |
| with trayslide up | |
| with trayslide dow | |
| Work surf. Ht. mn | |
| Power rating kv | |
| including gantr | |
| excluding gantr | |
| 1/1 Gastronorm capacit | |
| Refrigerated storage cupboard unde | |

| DEL | VCRW3FC | VCRW4FC | VCRW5FC |
|------------------------|-------------|-------------|-------------|
| It kg | 127 | 170 | 212 |
| mm ding | 1160 | 1490 | 1815 |
| mm mm | 1310 680 | 1310 680 | 1310 680 |
| e up lown | 950 740 | 950 740 | 950 740 |
| mm | 900 | 900 | 900 |
| g kw Intry Intry | 2.2 2.1 | 2.2 2.1 | 2.7 2.1 |
| acity | 3 | 4 | 5 |
| rage nder | - | - | - |

| MODEL | VCGH2 | VCGH3 | VCGBH2 | VCGBH3 | VCGA2 | VCGA3 | VCGBA2 | VCGBA3 |
|------------------------------------|--------------------|---------------------|--------------------|---------------------|--------------------|---------------------|--------------------|---------------------|
| Weight kg | 96 | 132 | 90 | 126 | 90 | 120 | 84 | 114 |
| Length mm Depth mm Height mm | 830 680 1640 | 1160 680 1640 | 830 680 1640 | 1160 680 1640 | 830 680 1640 | 1160 680 1640 | 830 680 1640 | 1160 680 1640 |
| Power rating kw | 2.7 | 2.8 | 2.7 | 2.8 | 0.026 | 0.026 | 0.026 | 0.026 |
| Electrical Supply | 13amp | 13amp | 13amp | 13amp | 13amp | 13amp | 13amp | 13amp |
| | | | | | | | | |

Versicarte Plus





Polar plates must firstly be charged for 12/24 hours in a deep freeze. They are then placed inside the well where they give off a steady flow of cold air for a minimum of two hours. Once used, other polar plates can then be substituted thus keeping the well cold.



Interior view of polar well.



Ambient Storage Cupboard With Plain Top Models VCSC2, VCSC3, VCSC4, VCSC5


• Sliding doors are removable for easy cleaning.

down trav slide and transfers.

- All internal grid shelves are removable for cleaning.
- Optional illuminated gantry with on/off switch indicating power is on, complete with interchangeable curved glass screen.



Rear view of storage cupboard.



Internal fan.



Optional Solid Drop Down Tray Slide



Optional Triple Tube Drop Down Tray Slide



VCHC4 with optional coach lines and solid drop down tray slide.

Hot Cupboard

Models, VCHC2, VCHC3, VCHC4, VCHC5

- Hot cupboard can store pre-heated food for serving.
 Thermostatically controlled hot cupboard with fan assisted removable heating unit.
- Sliding doors are removable for easy cleaning.
- All internal grid shelves are removable for cleaning.
- The heating unit (located on the base of the cupboard) can easily be removed for maintenance and cleaning.
- Optional quartz heated gantry with interchangeable curved glass screen.

MODEL

| Weight kg |
|-----------------------|
| Length mm |
| Height including |
| canopy mm |
| Depth mm |
| with tray slides up |
| with tray slides down |
| Work surf. Ht. mm |
| |

Power rating kw including canopy

1/1 Gastronorm

capacity

Refrigerated storage cupboard under

| | VCRW4C erated Salad Bar A | VCRW5C mbient Shelf Under |
|----------------------------|------------------------------|------------------------------|
| 137 | 180 | 222 |
| 1160 | 1490 | 1815 |
| 1880 680 1220 800 | 1880 680 1220 800 | 1880 680 1220 800 |
| 900 | 900 | 900 |
| 1.5 | 1.5 | 2.0 |
| 3 | 4 | 5 |
| - | - | - |

VCPW3C - shown

optional Triple Tube

c/w Canopy and

Drop Down Tray

Slides to both sides

and optional Salad

(fully adjustable) and

Bar Island Shelf

optional transfers.

| | CRW4RC erated Salad Bar Ro | |
|----------------------------|-------------------------------|----------------------------|
| 137 | 180 | 222 |
| 1160 | 1490 | 1815 |
| 1880 680 1220 800 | 1880 680 1220 800 | 1880 680 1220 800 |
| 900 | 900 | 900 |
| 1.5 | 1.5 | 2.0 |
| 3 | 4 | 5 |
| <u></u> | <u></u> | <u></u> |

| | VCPW3C ad Bar Ambient Sh | | VCPW5C |
|-----------------------------------|-----------------------------------|-----------------------------------|-----------------------------------|
| 68 | 97 | 127 | 155 |
| 830 | 1160 | 1490 | 1815 |
| 1880 680 1220 800 900 | 1880 680 1220 800 900 | 1880 680 1220 800 900 | 1880 680 1220 800 900 |
| 0.026 | 0.026 | 0.052 | <u>0.052</u> 5 |
| - | - | - | - |

| VCSC2 | VCSC3 | VCSC4 | VCSC5 |
|---------------------------|---------------------------|---------------------------|---------------------------|
| 30 | 45 | 60 | 75 |
| 830 | 1160 | 1490 | 1815 |
| 1310 680 950 740 | 1310 680 950 740 | 1310 680 950 740 | 1310 680 950 740 |
| 900 | 900 | 900 | 900 |
| 0.026 | 0.026 | 0.052 | 0.052 |
| 2 | 3 | 4 | 5 |
| | | | |

| VCHC2 | VCHC3 | VCHC4 | VCHC5 |
|---------------------------|----------------------------------|----------------------------------|----------------------------------|
| 34 | 51 | 68 | 85 |
| 830 | 1160 | 1490 | 1815 |
| 1310 680 950 740 | 1310 680 950 740 900 | 1310 680 950 740 900 | 1310 680 950 740 900 |
| 1.7 1.5 2 | 1.9 1.5 3 | 1.9 1.5 4 | 2.1 1.5 5 |
| | | | |

Weight kg

Length mm

Height including gantry mm

Depth mm

with tray slide up with tray slide down

Work surf. Ht. mm

Power rating kw including gantry excluding gantry


1/1 Gastronorm capacity

MODEL

See price list for detailed specification

Versicarte Plus







Left handed

Plan view

Computer port in work surface




Optional lockable cash drawer




Transposeable Right Angle Corner Section Model VCCU - Shown with optional triple tube drop down tray slide

 Transposable right angle corner section creating a 90° change in direction.

Plan view







Optional Triple Tube Drop Down Tray slide

All Versicarte units are available as low level units for children. Add "B" to standard code ie VCBM4(B). Height = 800mm.

Versiclear **Versiclear Unit** Models VCPF and VCPB

800mm high

The stylish new catering waste trolley, designed to make it easy for school children to clear away after meals. It features simple to follow graphics and layout, tough and durable construction, attractive design, easy to clean stainless steel surfaces and structure, two heights, for juniors and seniors, wide range of colours and designs, ease of manoeuvrability and braked castors.





Cashier Section with Cable Port and Double Electrical Socket

Model's, VCCS(R), VCCS(L) (R) denotes right handed, (L) denotes left handed

- Suitable for most types of cash registers, barcode scanners and Epos systems.
- Fitted with a cable port and double electric socket as standard.
- Complete with sloping rubber footrest.



Low Level Infill Unit Model VCSL

- Low unit can be used to create a split level effect when used in line with any other unit in the range.
- Storage space underneath.

VCCS(R) VCCS(L)

| MODEL | |
|----------------------|--|
| Weight kg | |
| Length mm | |
| Height including | |
| gantry mm | |
| Depth mm | |
| with tray slide up | |
| with tray slide down | |

Work surf. Ht. mm

Power rating kw including gantry excluding gantry

No. of panels

| ¥000(It) | ¥003(L) | *000 | VOOL |
|------------|------------|------------|------|
| 62 | 62 | 72 | 25 |
| 1160 | 1160 | 1380 | 680 |
| - | - | - | - |
| 680 950 | 680 950 | 480 750 | 680 |
| 740 | 740 | 540 | - |
| 900 | 900 | 900 | 500 |
| | | | |
| - | - | - | - |
| - | - | - | - |
| - | - | - | - |
| | | | |



VCBM4(B) shown with optional triple tube drop down tray slide and transfers.

800mm high to the work surface.

are available at extra cost.

Optional Solid Drop

Low level Versicarte Plus

Low level modules designed for use with younger children.

such as cartoon characters and logos can be applied using

durable vinyl. All the specifications and options, as per full

Advantages include the easy and safe viewing of food. Designs

size modules, are available. Low level Versicarte Plus units are

Note: Refrigerated units are designed for straight through ventilation. If

units are to be placed against a wall alternative ventilation arrangements

Coachlines and bespoke designs can be incorporated at extra cost.




Above: Low level Versicarte Plus height comparison with full size module

| VCPF | VCPB |
|---------------------|--------------------|
| 63 | 56 |
| 1650 1060 550 | 1650 960 550 |
| - - | - |
| 900 | 800 |
| | |
| | |

MODEL Weight kg Length mm trayslide up with trayslide down Work surf. Ht. mm Power rating kw No. of plates








Regeneration & Keep Hot



General Fabrication



Countering