



SILVERLINK 600

Whether you're cooking eggs, bacon, burgers or vegetables, the versatile Silverlink 600 Electric Griddle won't let you down. It features two separately controlled heat zones, which give you the option of operating either zone independently to provide a smaller cooking area during quiet periods as well as offering versatility when cooking two separate meals simultaneously. The two-zone system is designed to give you maximum flexibility during service. The griddle, perfect for cafes, pubs and restaurants, is also thermostatically controlled to give accurate temperatures during the cooking process for consistent results.

PRODUCT OPTIONS AND ACCESSORIES

- SB7 750 GRIDDLE SPLASHB
- CC7 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal with Doors - W 750 mm
- CN7 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 750 mm
- SLS7 Lincat Silverlink 600 Free-standing Floor Stand - for units W 750 mm
- HC7 Lincat Silverlink 600 Free-standing Heated Open-Top Pedestal with Doors - W 750 mm - 0.5 kW
- HCL7 Lincat Silverlink 600 Free-standing Heated Pedestal with Legs and Doors - W 750 mm - 0.75 kW

PRODUCT FEATURES

- Two separately controlled heat zones give you the option of operating either zone independently to provide a smaller cooking area during quiet periods as well as offering versatility when cooking two separate meals simultaneously
- 12 mm thick machined steel plate providing even heat distribution and an easy to clean surface
- The plate is fully welded into the frame to prevent leaks and places where food and carbon can build up
- 2 cooking zone to give maximum flexibility during service
- Thermostatically controlled to give accurate temperatures during the cooking process for consistent results
- Front mounted control for easy of use during cooking

WEIGHTS & DIMENSIONS

Width	750 mil
Depth	620 mil
Height	330 mil
Weight	48.9 kg

SHIPPING DETAILS

Ship Width	85.5 cm
Ship Depth	70 cm
Ship Height	63.5 cm
Ship Weight	53.79 kg
Number of Shipment Parcels	1
Ship Method	Small Parcel (FedEx, UPS, DHL)
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

WATER, PLUMBING, AND DRAINAGE SPECS

Water Line Required	No
Drain Line Required	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Type	Electric
Electrical Amps Per Conductor	Single Phase 26.1/Three Phase L1=13.0; L2=13.0; L3=N/
Electrical Total Amperage	26.1 A
Electrical Volts	230-400V
Electrical Total Wattage	6000 W

Electrical Kilowatts	6 kW
Electrical Plug Type	Hardwired
Number of Electrical Plugs	Not Applicable
Number of Electrical Conductor Wires	1
Dedicated Circuit Required	Yes
Electrical Remarks	Single, Three

ADDITIONAL SPECIFICATIONS

Control Type	Rotary Control Knob
Cooking Area Plate Depth	405 mm
Cooking Area Plate Width	712 mm
Cooking Plate Finish Material Type	Polished Steel
Food Production Rate	190 x 115g [4oz] burgers [frozen] per hour
Lower Platen Surface Type	Smooth

Number Of Controls	2
Number of Heating Zones	2
Plate Shape	Rectangle
Plate Thickness	12 mm
Temperature Maximum	250 °C
Temperature Minimum	50 °C
Thermostat Element Location	Under Plate Mount

BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

TECHNICAL DRAWING

